

ARDEX MC™ RAPID

One-Coat Moisture Control System for Concrete to Receive ARDEX Underlayments

The ARDEX MC™ RAPID Moisture Control System is formulated to suppress excessive moisture vapor emissions in new or existing concrete prior to installing an ARDEX underlayment with flooring. It is especially suited to critical installations where the construction schedule does not allow adequate drying of concrete.

Key Features

- 100 % solids epoxy resin system
- No sand broadcast required for underlayment applications of 1/4" (6 mm) or less

Installation

- **Packaging:** 22 lb unit
- **Coverage on CSP 3 Prepared Concrete:** max. 270 sq. ft. (25 m²) per mixed unit
- **Working time:** 20 minutes
- **Pot life:** 20 minutes
- **Walkable:** 4 hours
- **Prime and install underlayment:** 4 hours

Performance

- **ASTM E96 perm rating:** 0.06 perms

ARDEX MC™ Moisture Control Systems

For RH readings up to 100%

Reduce vapor emissions to below maximum acceptable levels for floor coverings

Solvent free

Alkali resistant

Tenacious bond to substrate



AF-233 11/14

MOISTURE CONTROL SYSTEM



AMERICAS

888-512-7339

+1-724-203-5000

www.ardexamericas.com